

Genset  
Model: **YXP500RSC**

Enclosed set



Open set



Frequency	Phases	Power factor	Prime output	Standby output
50Hz	3	0.8	500 kVA / 400 kW	550 kVA / 440 kW

### Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity.

### Design features

- High quality assembly, providing stiffness and low vibration.
- Powder coated steel. Corrosion and scratch resistant.
- Compact and long service life.
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month YorPower Warranty.

### Design standards

- CE marking.
- ISO8528-1995.
- GB/T2820-1997.
- ISO 9001:2008 Registered Company.

### Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Coolant recovery tank.
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings.
- Integral fuel tank with fully bounded base protection.
- Fuel level sensor.
- Auto start control system with electronic digital control module DSE7420 as standard.
- Output circuit breaker.
- Emergency stop button.
- High engine temperature and low oil pressure shutdown system.
- 24V starter battery with leads and switch.

### Acoustic canopy features

- Water and dust proof design.
- Door locks.
- High quality sound absorbing and fire retardant inner material.
- Lifting lugs.
- Forklift holes in base.

\*\* The images above are for illustration purposes only.


## Engine data

Engine brand	Perkins	Total coolant capacity	58 Litres
Engine model	2506C-E15TAG2	Total lub oil capacity	62 Litres
Engine Speed	1500 RPM	Cooling air flow	722 m <sup>3</sup> /min
Number of cylinders	6	Exhaust gas flow (max)	98 m <sup>3</sup> /min
Aspiration	Turbo & Aftercooled	Exhaust gas temperature (max)	550 °C
Combustion system	Direct injection	Fuel cons. @ 100% Standby load	111 l/hr
Displacement	12.5 Litres	Fuel cons. @ 100% Prime load	100 l/hr
Governor type	Electronic	Fuel cons. @ 75% Prime load	76 l/hr
Cooling system	Water cooled	Fuel cons. @ 50% Prime load	53 l/hr

## Alternator data

Alternator brand	Leroy Somer	Number of wires	12
Alternator model	LSA47.2M7	AVR model	R 250
Excitation	Self excited	Voltage regulation	± 0.5%
Insulation class	H	Total Harmonic distortion	< 2% on load
Drip proof protection	IP23	Telephone interference	TIF < 50%
Winding pitch	2/3 (N° 6 or N° 6S)	Flanges and shield	Cast iron


## Enclosed set data



L x W x H (mm)    Weight    Fuel tank    Noise@7m

4592 x 1543 x 2562    5264 kg    1020 Litres    70.6 db

## Open set data



L x W x H (mm)    Weight    Fuel tank    Noise@7m

3765 x 1165 x 2145    3820 kg    950 Litres    109 db

\*\* Due to constant innovation, design and specifications are subject to change without notice. All weights, dimensions and noise levels are subject to a 10% tolerance.

Distributor Address:

# YORPOWER

YorPower Ltd,  
Electricity Building, Unit 2 Hurricane Close,  
Sherburn in Elmet, Leeds LS25 6PB, UK  
T : +44 (0)1977 688155  
E: sales@yorpower.com  
www.yorpower.com